

Model Diameter Ref.	SPR	Nominal Diameter (m)	Nominal Base Area (m <sup>2</sup> )	Model Height Ref. and nominal height in metres									
				05 SR20	10 SR20	15 SR20	20 SR20	25 SR20	30 SR20	35 SR20	40 SR20	45 SR20	50 SR20
				1.933 m	3.333 m	4.733 m	6.133 m	7.533 m	8.933 m	10.333 m	11.733 m	13.133 m	14.533 m
11	4	3.416	9.162	9.5	16.7	23.9	31.1	38.3	45.6	52.8	60.0	67.2	74.4
14	5	4.269	14.32	16.9	29.7	42.5	55.3	68.2	81.0	93.8	106.7	119.5	132.3
17	6	5.123	20.62	26.4	46.4	66.4	86.5	106.5	126.6	146.6	166.7	186.7	206.7
20	7	5.977	28.06	38.0	66.8	95.7	124.5	153.4	182.3	211.1	240.0	268.8	297.7
22	8	6.831	36.65	51.7	90.9	130.2	169.5	208.8	248.1	287.4	326.6	365.9	405.2
25	9	7.685	46.38	67.5	118.8	170.1	221.4	272.7	324.0	375.3	426.6	477.9	529.2
28	10	8.539	57.26	85.4	150.3	215.3	280.2	345.1	410.1	475.0	540.0	604.9	669.8
31	11	9.393	69.29	105.4	185.6	265.8	345.9	426.1	506.3	586.4	666.6	746.8	827.0
34	12	10.247	82.46	127.6	224.6	321.6	418.6	515.6	612.6	709.6	806.6	903.6	1000.6
36	13	11.100	96.78	151.8	267.3	382.7	498.1	613.6	729.0	844.5	959.9	1075.4	1190.8
39	14	11.954	112.2	178.2	313.7	449.1	584.6	720.1	855.6	991.1	1126.6	1262.1	1397.5
42	15	12.808	128.8	206.6	363.8	520.9	678.0	835.2	992.3	1149.4	1306.6	1463.7	1620.8
45	16	13.662	146.6	237.2	417.6	598.0	778.3	958.7	1139.1	1319.5	1499.9	1680.3	1860.6
48	17	14.516	165.5	269.9	475.1	680.4	885.6	1090.8	1296.1	1501.3	1706.5	1911.8	2117.0
50	18	15.370	185.5	304.7	536.4	768.1	999.7	1231.4	1463.1	1694.8	1926.5	2158.2	2389.9
53	19	16.224	206.7	341.6	601.3	861.1	1120.8	1380.6	1640.3	1900.1	2159.8	2419.6	2679.3
56	20	17.078	229.1	380.6	670.0	959.4	1248.8	1538.2	1827.6	2117.1	2406.5	2695.9	2985.3
59	21	17.931	252.5	421.7	742.4	1063.1	1383.7	1704.4	2025.1	2345.8	2666.4	2987.1	3307.8
62	22	18.785	277.2	464.9	818.5	1172.0	1525.6	1879.1	2232.7	2586.2	2939.8	3293.3	3646.9
64	23	19.639	302.9	510.2	898.3	1286.3	1674.3	2062.3	2450.4	2838.4	3226.4	3614.4	4002.4
67	24	20.493	329.8	557.7	981.8	1405.9	1830.0	2254.1	2678.2	3102.3	3526.4	3950.5	4374.6
70	25	21.347	357.9	607.2	1069.0	1530.8	1992.6	2454.3	2916.1	3377.9	3839.7	4301.5	4763.2
73	26	22.201	387.1	658.9	1160.0	1661.0	2162.1	2663.1	3164.2	3665.3	4166.3	4667.4	5168.4
76	27	23.055	417.5	712.7	1254.6	1796.6	2338.5	2880.5	3422.4	3964.3	4506.3	5048.2	5590.2
78	28	23.909	449.0	768.5	1353.0	1937.4	2521.8	3106.3	3690.7	4275.2	4859.6	5444.0	6028.5
81	29	24.762	481.6	826.5	1455.0	2083.6	2712.1	3340.6	3969.2	4597.7	5226.2	5854.8	6483.3

**Notes:**

1. The model reference consists of a diameter ref. in feet followed by a height ref. in feet - e.g. Model 5620 is 17.078m (approximately 56ft) diameter x 5.626m (approximately 20ft) high.
2. The nominal height is measured from the centreline of the bottom horizontal row of bolt holes to the top edge of the top sheet.
3. The nominal volumes shown are based on nominal heights with a rebate design and a total embedment depth of 93mm with no allowance for freeboard.
4. The overall structure height over angles will depend on the chosen roof structure and top stiffener and foundation angles. Half sheets are available to give intermediate heights.
5. The diameters, nominal heights and capacities are shown for guidance only. PermaStore distributors can refer to the PermaStore Portal for further information otherwise please contact PermaStore for project specific information.

Model Diameter Ref.	SPR	Nominal Diameter (m)	Nominal Base Area (m <sup>2</sup> )	Model Height Ref. and nominal height in metres									
				05 SR20	10 SR20	15 SR20	20 SR20	25 SR20	30 SR20	35 SR20	40 SR20	45 SR20	50 SR20
				1.933 m	3.333 m	4.733 m	6.133 m	7.533 m	8.933 m	10.333 m	11.733 m	13.133 m	14.533 m
84	30	25.616	515.4	886.6	1560.8	2235.1	2909.3	3583.5	4257.7	4932.0	5606.2	6280.4	6954.7
87	31	26.470	550.3	948.8	1670.3	2391.9	3113.4	3834.9	4556.4	5278.0	5999.5	6721.0	7442.6
90	32	27.324	586.4	1013.1	1783.5	2554.0	3324.4	4094.8	4865.3	5635.7	6406.1	7176.6	7947.0
92	33	28.178	623.6	1079.5	1900.5	2721.4	3542.3	4363.3	5184.2	6005.2	6826.1	7647.0	8468.0
95	34	29.032	662.0	1148.1	2021.1	2894.2	3767.2	4640.3	5513.3	6386.4	7259.4	8132.4	9005.5
98	35	29.886	701.5	1218.7	2145.5	3072.2	3999.0	4925.7	5852.5	6779.3	7706.0	8632.8	9559.6
101	36	30.740	742.1	1291.4	2273.5	3255.6	4237.7	5219.8	6201.8	7183.9	8166.0	9148.1	10130.2
104	37	31.594	783.9	1366.3	2405.3	3444.3	4483.3	5522.3	6561.3	7600.3	8639.3	9678.3	10717.3
106	38	32.447	826.9	1522.3	2680.0	3837.6	4995.3	6152.9	7310.6	8468.2	9625.9	10783.5	11941.2
109	39	33.301	871.0	1603.5	2822.9	4042.3	5261.6	6481.0	7700.4	8919.8	10139.2	11358.5	12577.9
112	40	34.155	916.2	1686.8	2969.5	4252.2	5534.9	6817.6	8100.4	9383.1	10665.8	11948.5	13231.2
115	41	35.009	962.6	1772.2	3119.8	4467.5	5815.1	7162.8	8510.4	9858.1	11205.7	12553.4	13901.0
118	42	35.863	1010.1	1859.7	3273.9	4688.1	6102.2	7516.4	8930.6	10344.8	11759.0	13173.2	14587.4
120	43	36.717	1058.8	1949.3	3431.6	4914.0	6396.3	7878.6	9361.0	10843.3	12325.6	13808.0	15290.3
123	44	37.571	1108.6	2041.0	3593.1	5145.2	6697.3	8249.3	9801.4	11353.5	12905.6	14457.7	16009.8
126	45	38.425	1159.6	2134.8	3758.3	5381.7	7005.1	8628.6	10252.0	11875.4	13498.9	15122.3	16745.8
129	46	39.278	1211.7	2230.8	3927.1	5623.5	7319.9	9016.3	10712.7	12409.1	14105.5	15801.9	17498.3
132	47	40.132	1265.0	2328.8	4099.7	5870.7	7641.6	9412.6	11183.5	12954.5	14725.4	16496.4	18267.3
134	48	40.986	1319.4	2429.0	4276.1	6123.2	7970.3	9817.4	11664.5	13511.6	15358.7	17205.8	19053.0
137	49	41.840	1374.9	2531.2	4456.1	6381.0	8305.8	10230.7	12155.6	14080.5	16005.3	17930.2	19855.1
140	50	42.694	1431.6	2635.6	4639.8	6644.1	8648.3	10652.6	12656.8	14661.0	16665.3	18669.5	20673.8
143	51	43.548	1489.4	2742.1	4827.3	6912.5	8997.7	11082.9	13168.1	15253.4	17338.6	19423.8	21509.0
146	52	44.402	1548.4	2850.6	5018.4	7186.2	9354.0	11521.8	13689.6	15857.4	18025.2	20193.0	22360.8
148	53	45.256	1608.5	2961.3	5213.3	7465.3	9717.2	11969.2	14221.2	16473.2	18725.1	20977.1	23229.1
151	54	46.109	1669.8	3074.1	5411.9	7749.6	10087.4	12425.1	14762.9	17100.6	19438.4	21776.1	24113.9
154	55	46.963	1732.2	3189.1	5614.2	8039.3	10464.5	12889.6	15314.7	17739.9	20165.0	22590.1	25015.3

**Notes:**

1. The model reference consists of a diameter ref. in feet followed by a height ref. in feet - e.g. Model 5620 is 17.078m (approximately 56ft) diameter x 5.626m (approximately 20ft) high.
2. The nominal height is measured from the centreline of the bottom horizontal row of bolt holes to the top edge of the top sheet.
3. The nominal volumes shown are based on nominal heights with a rebate design and a total embedment depth of 93mm with no allowance for freeboard.
4. The overall structure height over angles will depend on the chosen roof structure and top stiffener and foundation angles. Half sheets are available to give intermediate heights.
5. The diameters, nominal heights and capacities are shown for guidance only. Permastore distributors can refer to the Permastore Portal for further information otherwise please contact Permastore for project specific information.

Model Diameter Ref.	SPR	Nominal Diameter (m)	Nominal Base Area (m <sup>2</sup> )	Model Height Ref. and nominal height in metres									
				05 SR20	10 SR20	15 SR20	20 SR20	25 SR20	30 SR20	35 SR20	40 SR20	45 SR20	50 SR20
				1.933 m	3.333 m	4.733 m	6.133 m	7.533 m	8.933 m	10.333 m	11.733 m	13.133 m	14.533 m
157	56	47.817	1795.8	3306.1	5820.2	8334.3	10848.4	13362.6	15876.7	18390.8	20904.9	23419.1	25933.2
160	57	48.671	1860.5	3425.2	6029.9	8634.6	11239.3	13844.1	16448.8	19053.5	21658.2	24262.9	26867.6
162	58	49.525	1926.4	3546.4	6243.3	8940.3	11637.2	14334.1	17031.0	19727.9	22424.8	25121.7	27818.6
165	59	50.379	1993.4	3669.8	6460.5	9251.2	12041.9	14832.6	17623.3	20414.0	23204.7	25995.5	28786.2
168	60	51.233	2061.5	3795.2	6681.3	9567.5	12453.6	15339.7	18225.8	21111.9	23998.0	26884.1	29770.2
171	61	52.087	2130.8	3922.8	6905.9	9889.0	12872.1	15855.3	18838.4	21821.5	24804.6	27787.7	30770.8
174	62	52.940	2201.2	4052.5	7134.2	10215.9	13297.6	16379.4	19461.1	22542.8	25624.5	28706.3	31788.0
176	63	53.794	2272.8	4184.2	7366.2	10548.1	13730.1	16912.0	20093.9	23275.9	26457.8	29639.8	32821.7
179	64	54.648	2345.5	4318.1	7601.9	10885.6	14169.4	17453.1	20736.9	24020.7	27304.4	30588.2	33871.9
182	65	55.502	2419.4	4454.1	7841.3	11228.5	14615.6	18002.8	21390.0	24777.2	28164.3	31551.5	34938.7
185	66	56.356	2494.4	4592.2	8084.4	11576.6	15068.8	18561.0	22053.2	25545.4	29037.6	32529.8	36022.0
188	67	57.210	2570.6	4732.4	8331.3	11930.1	15528.9	19127.7	22726.6	26325.4	29924.2	33523.0	37121.8
190	68	58.064	2647.9	4874.8	8581.8	12288.9	15995.9	19703.0	23410.0	27117.1	30824.1	34531.2	38238.2
193	69	58.918	2726.3	5019.2	8836.1	12653.0	16469.8	20286.7	24103.6	27920.5	31737.4	35554.3	39371.1
196	70	59.772	2805.9	5165.7	9094.1	13022.4	16950.7	20879.0	24807.3	28735.6	32664.0	36592.3	40520.6
199	71	60.625	2886.7	5314.4	9355.7	13397.1	17438.5	21479.8	25521.2	29562.5	33603.9	37645.2	41686.6
202	72	61.479	2968.6	5465.1	9621.1	13777.1	17933.1	22089.1	26245.1	30401.1	34557.1	38713.1	42869.1
205	73	62.333	3051.6	5618.0	9890.3	14162.5	18434.7	22707.0	26979.2	31251.5	35523.7	39796.0	44068.2
207	74	63.187	3135.8	5773.0	10163.1	14553.2	18943.3	23333.4	27723.5	32113.6	36503.6	40893.7	45283.8
210	75	64.041	3221.1	5930.1	10439.6	14949.2	19458.7	23968.3	28477.8	32987.4	37496.9	42006.4	46516.0
213	76	64.895	3307.6	6089.2	10719.9	15350.5	19981.1	24611.7	29242.3	33872.9	38503.5	43134.1	47764.7
216	77	65.749	3395.2	6250.5	11003.8	15757.1	20510.3	25263.6	30016.9	34770.1	39523.4	44276.7	49029.9
219	78	66.603	3483.9	6413.9	11291.5	16169.0	21046.5	25924.1	30801.6	35679.1	40556.6	45434.2	50311.7
221	79	67.456	3573.9	6579.5	11582.9	16586.3	21589.6	26593.0	31596.4	36599.8	41603.2	46606.6	51610.0
224	80	68.310	3664.9	6747.1	11878.0	17008.8	22139.7	27270.5	32401.4	37532.3	42663.1	47794.0	52924.9
227	81	69.164	3757.1	6916.8	12176.8	17436.7	22696.6	27956.6	33216.5	38476.4	43736.4	48996.3	54256.3

**Notes:**

1. The model reference consists of a diameter ref. in feet followed by a height ref. in feet - e.g. Model 5620 is 17.078m (approximately 56ft) diameter x 5.626m (approximately 20ft) high.
2. The nominal height is measured from the centreline of the bottom horizontal row of bolt holes to the top edge of the top sheet.
3. The nominal volumes shown are based on nominal heights with a rebate design and a total embedment depth of 93mm with no allowance for freeboard.
4. The overall structure height over angles will depend on the chosen roof structure and top stiffener and foundation angles. Half sheets are available to give intermediate heights.
5. The diameters, nominal heights and capacities are shown for guidance only. Permastore distributors can refer to the Permastore Portal for further information otherwise please contact Permastore for project specific information.

Model Diameter Ref.	SPR	Nominal Diameter (m)	Nominal Base Area (m <sup>2</sup> )	Model Height Ref. and nominal height in metres									
				05 SR20	10 SR20	15 SR20	20 SR20	25 SR20	30 SR20	35 SR20	40 SR20	45 SR20	50 SR20
				1.933 m	3.333 m	4.733 m	6.133 m	7.533 m	8.933 m	10.333 m	11.733 m	13.133 m	14.533 m
230	82	70.018	3850.4	7088.7	12479.3	17869.9	23260.5	28651.1	34041.7	39432.3	44823.0	50213.6	55604.2
233	83	70.872	3944.9	7262.6	12785.5	18308.4	23831.3	29354.2	34877.1	40400.0	45922.9	51445.8	56968.7
235	84	71.726	4040.6	7438.7	13095.4	18752.2	24409.0	30065.8	35722.6	41379.3	47036.1	52692.9	58349.7
238	85	72.580	4137.3	7616.8	13409.1	19201.4	24993.6	30785.9	36578.2	42370.4	48162.7	53955.0	59747.2
241	86	73.434	4235.3	7797.1	13726.5	19655.8	25585.2	31514.5	37443.9	43373.2	49302.6	55231.9	61161.3
244	87	74.287	4334.3	7979.5	14047.5	20115.6	26183.6	32251.7	38319.7	44387.8	50455.8	56523.9	62591.9

**Notes:**

1. The model reference consists of a diameter ref. in feet followed by a height ref. in feet - e.g. Model 5620 is 17.078m (approximately 56ft) diameter x 5.626m (approximately 20ft) high.
2. The nominal height is measured from the centreline of the bottom horizontal row of bolt holes to the top edge of the top sheet.
3. The nominal volumes shown are based on nominal heights with a rebate design and a total embedment depth of 93mm with no allowance for freeboard.
4. The overall structure height over angles will depend on the chosen roof structure and top stiffener and foundation angles. Half sheets are available to give intermediate heights.
5. The diameters, nominal heights and capacities are shown for guidance only. Permastore distributors can refer to the Permastore Portal for further information otherwise please contact Permastore for project specific information.