Application Guide - Glass Grades

APPLICATION	ECOFUSION®	ISOFUSION® V700	TRIFUSION®	TRIFUSION® PLUS	INTERNAL COLOURS
Farm Digesters using Agricultural Waste	■				
Farm Digesters using any other Waste Streams		■			
Edible / Vegetable Oils		■			
Dry Bulk Solids		■			
Storm / Fire Water		■			
Potable Water (NSF / ANSI 61)		■			
Drinking Water (DWI, Reg 31 Approved)		■			
Filter Tanks		■			
Municipal Sludge Storage (Open Topped)		■			
Municipal Sludge Treatment (Open Topped)		■			
Municipal Mesophilic Digester (Liquid Zone)		■			
Municipal Backwash Effluent		■			
Municipal Sludge Cake Storage		■			
Farm Digesters (Roof & Rings Exposed to Gaseous Zone)			■		
Municipal Sludge Storage (Roof & Rings Exposed to Gaseous Zone)			■		
Municipal Sludge Treatment (Roof & Rings Exposed to Gaseous Zone)			■		
Municipal Mesophilic Digester (Roof & Rings Exposed to Gaseous Zone)			■		
Thermophilic Digester (Liquid Zone)			■		
Industrial Effluent and/or Aeration Process			■		
Food Process Washings			■		
Liquid Leachates			■		
Borehole / Brackish / Seawater			■		
Thermophilic Digester (Roof & Rings Exposed to Gaseous Zone)				■	
Aggressive / Chemical Industrial Effluent				■	

20 - C - 40
(RAL 5013)

RAL 160 - 40 - 15

Standard External Colours	20-C-40 (RAL 5013)	12-B-29 (RAL 6006)
Optional External Colours	MUNSELL 7.5YR 8/4	00-A-05 (RAL 7004)
		14-C-39 (RAL 6028)

Further external colours are available on request.
All colour identification numbers are the closest visual match only.
All panel exteriors are Glass-Fused-to-Steel environmental specification.
Optional colours at additional cost.